NSN 5905-01-077-8626

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-077-8626

Financian to Continuous Continuou	Tompurature Coefficient Of Resistance In Rom Per Dog Colsius
Electrical Resistance: 756.000 klokhms Resistance Tolorance in Percent: -1.000/+1.0000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+15.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0.0 Tempurature Range Of Tempurature Coefficient in	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Diameter: 0.375 inches Power Dissipation Rating In Watts: 0.550 free air Unpackaged Unit Weight: 0.750 grams Style Dosignator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-390172 government specification Shelf Life:	
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire laad Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: 1.500 inches Body Diamete: 0.138 inches Body Diamete: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating in Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Avial terminal each end Test Data Document: 1349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 8149-mil-r-39017/2 government specification Shelf Life:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Diameter: 0.138 inches Power Dissipation Rating In Watts: 0.375 inches Power Dissipation Rating In Watts: 0.750 grams Style Designator: 4 Visial terminal each end Test Data Document: 1 1494-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain envirronmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-390172 government specification Shelf Life:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.10 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 0.138 indrens end	
70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', "average", ", etc.). Specification Data: 81349-mil-r-390172 government specification Shelf Life:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 ree air Unpackaged Unit Weight: 0.750 grands Style Designator: Axial terminal each end Test Data Document: 81349-mili-r-390177 government specification in Stat at reflect specification type data in specification verwironmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81499-mili-r-3901772 government specification	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.550 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
rempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.7500 grea in Companie (Includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
-50.0/+150.0 inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating in Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 pecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mili-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mili-r-39017/2 government specification Shelf Life:	
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 yspecification (includes engineering type bulletins, brochures, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification (Shelf Life:	
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ervironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	·
O.375 inches Power Dissipation Rating In Watts: O.500 free air Unpackaged Unit Weight: O.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
0.500 free air Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Unpackaged Unit Weight: 0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
0.750 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
Specification Data: 81349-mil-r-39017/2 government specification Shelf Life:	
81349-mil-r-39017/2 government specification Shelf Life:	
Shelf Life:	
N/a	
H-M-OCH	
Unit Of Measure:	Unit Ot Measure:
Demilitarization:	

No

NSN 5905-01-077-8626

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0