NSN 5905-01-077-9703

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-077-9703 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.188 inches **Body Diameter:** 0.375 inches **Body Length:** Between 0.190 inches and 0.210 inches **Actuator Type:** Integral knob **Effective Electrical Rotation In Deg Angular Rotation:** 190.0 **Center To Center Distance Between Terminals:** Between 0.190 inches and 0.210 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 10.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.090 inches and 0.110 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

NSN 5905-01-077-9703

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0