

View Online at <https://aerobasegroup.com/nsn/5905-01-078-1549>

Section Quantity:

2

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

Overall Length:

2.960 inches

Overall Height:

1.125 inches

Overall Width:

0.625 inches

Shaft Diameter:

0.125 inches

Shaft Length:

1.781 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.125 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Undercut Diameter:

0.078 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Fragility Factor:

Moderately rugged

Undercut Length:

0.375 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Cubic Measure:

0.439 cubic inches

Electrical Resistance Per Section:

10.000 percent, rated amperes c and better

Rotary Actuator Travel In Angular Deg:

300.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+5.0 -55 degrees celsius all sections and +0.0/+3.0 -25 degrees celsius all sections and -1.5/+1.5 0 degrees celsius all sections and -2.0/+2.0 85 degrees celsius all sections and -3.0/+3.0 120 degrees celsius all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary at 10'30 oclock

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0