

View Online at <https://aerobasegroup.com/nsn/5905-01-078-1549>

**Section Quantity:**

2

**Body Style:**

Rectangular w/bushing

**Reliability Indicator:**

Not established

**Overall Length:**

2.960 inches

**Overall Height:**

1.125 inches

**Overall Width:**

0.625 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

1.781 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

1.125 inches

**Body Width:**

0.625 inches

**Body Height:**

0.625 inches

**Undercut Diameter:**

0.078 inches

**Shaft Style:**

Round, stepped

**Actuator Type:**

Dual concentric

**Effective Electrical Rotation In Deg Angular Rotation:**

260.0

**Fragility Factor:**

Moderately rugged

**Undercut Length:**

0.375 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.439 cubic inches

**Electrical Resistance Per Section:**

10.000 percent, rated amperes c and better

**Rotary Actuator Travel In Angular Deg:**

300.0

**Resistance Temperature Characteristic Range Per Section In Percent:**

+0.0/+5.0 -55 degrees celsius all sections and +0.0/+3.0 -25 degrees celsius all sections and -1.5/+1.5 0 degrees celsius all sections and -2.0/+2.0 85 degrees celsius all sections and -3.0/+3.0 120 degrees celsius all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 all sections

**Power Dissipation Rating Per Section In Watts:**

0.5 7th secondary at 10'30 oclock

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0