NSN 5905-01-078-8028

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-078-8028

Townwesture Coefficient Of Registeres In Rum Rev Rev Calaine.
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0 Floatrical Resistance:
Electrical Resistance: 31.600 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+150.0
Inclosure Method:
Encapsulated Torminal Types
Terminal Type: Wire lead
Reliability Indicator: Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
1.500 inches
Body Diameter:
0.090 inches
Body Length:
0.250 inches
Power Dissipation Rating In Watts:
0.250 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-milr39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39017/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.

A001a0

Fiig:

NSN 5905-01-078-8028

Film Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-r-39017 spec.