## NSN 5905-01-078-8514

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-078-8514

Section Quantity:				
2				
Body Style:				
Cylindrical bushing mounted				
Reliability Indicator:				
Not established				
Body Diameter:				
1.125 inches				
Shaft Diameter:				
0.250 inches				
Shaft Length:				
0.125 inches				
Mounting Bushing Length:				
0.375 inches				
Body Length:				
1.156 inches				
Shaft Style:				
Round, slotted				
Actuator Type:				
Single shaft				
Maximum Starting Torque:				
15.00 inch-ounces				
Maximum Running Torque:				
6.00 inch-ounces				
Maximum Stop Torque:				
8.00 inch-ounces				
Screw Thread Diameter:				
0.375 inches				
Screw Thread Series Designator:				
Unef				
Screw Thready Qty Per Inch (tpi):				
32.0				
Terminal Location:				
Radially positioned over less than half the circumference				
Mounting Method:				
Standard bushing				
Electrical Resistance Per Section:				
8500.000 ohms all sections				
Power Dissipation Rating Per Section In Watts:				
7.0 free air all sections				
Resistance Tolerance Per Section In Percent:				

-10.0/+10.0 all sections

## NSN 5905-01-078-8514

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0