

View Online at <https://aerobasegroup.com/nsn/5905-01-079-3061>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 0.844 inches and 0.906 inches

Shaft Diameter:

0.128 inches

Shaft Length:

0.880 inches

Mounting Bushing Length:

0.250 inches

Body Length:

Between 0.626 inches and 0.752 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

Between 0.235 inches and 0.265 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

75.0 ohms single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

12.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0