Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-079-3194

Section Quantity:

1

Body Style: Cylindrical servo mounted Reliability Indicator: Not established

Pilot Diameter:

Between 1.5610 inches and 1.5620 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Undercut Diameter:

Between 1.595 inches and 1.605 inches

Undercut Width:

0.0730 inches

Body Diameter:

Between 1.754 inches and 1.755 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

Between 0.594 inches and 0.656 inches

Body Length:

Between 0.962 inches and 0.978 inches

Mounting Lip Diameter:

Between 1.5610 inches and 1.5620 inches

Mounting Lip Depth:

Between 0.0880 inches and 0.0980 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Maximum Starting Torque:

0.70 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Shaft End Play:

0.00150 inches

Shaft Runout:

0.001 inches

NSN 5905-01-079-3194

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout:	
0.002 inches	
Pilot Diameter Runout:	
0.00150 inches	
Shaft Radial Play:	
0.002 inches	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Clamp ring	
Electrical Resistance Per Section:	
10.000 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
-0.50/+0.50 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent R	ated Power:
125.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg	. Celsius:
-300.0/+300.0 single section	0010100.
Power Dissipation Rating Per Section In Watts:	
1.5 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Fixed Tap Quantity Per Section:	
1 single section	
Tap Location Tolerance Per Section:	
-1.0/+1.0 ohms single section	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Tap Location From Ccw Terminal Per Section In Ohms:	
5000.0 single section	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Pow	ver-
60.0 single section	
Terminal Type And Quantity:	
3 turret	
Shelf Life:	
N/a	

- Unit Of Measure:
- ---

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0