NSN 5905-01-079-7233

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-079-7233 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.280 inches **Body Width:** 0.265 inches **Body Height:** 0.190 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Terminal Location:** Dual inline **Mounting Method: Terminal Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 270.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -150.0/+150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

Ambient Tempurature In Deg Celsius II
25.0 single section

Standard Taper Curve Per Section:
A single section

NSN 5905-01-079-7233

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0