Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-079-7234

Section	Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.125 inches

**Body Length:** 

0.265 inches

**Body Width:** 

0.280 inches

Body Height:

0.180 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

4320.0

Center To Center Distance Between Terminals:

0.200 inches

**Terminal Location:** 

Dual inline

**Mounting Method:** 

Terminal

Features Provided:

Humidity proof

**Electrical Resistance Per Section:** 

25.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

4320.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section



Standard Taper Curve Per Section:

A single section

**Special Features:** 

Two wiper terminals

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0