Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-080-1345

Section	Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.125 inches

**Body Length:** 

0.265 inches

**Body Width:** 

0.280 inches

**Body Height:** 

0.180 inches

Actuator Type:

#### Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

4320.0

**Center To Center Distance Between Terminals:** 

0.200 inches

**Terminal Location:** 

Dual inline

#### **Mounting Method:**

Terminal

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

20.000 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

4320.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

Any acceptable

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

## Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

#### **Actuator Travel Control Feature:**

Clutch



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

## **Special Features:**

Two wiper terminals

# Unpackaged Unit Weight:

2.0 grams

Precious Material And Location:

Terminal surfaces gold

**Precious Material:** 

Gold

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0