

View Online at <https://aerobasegroup.com/nsn/5905-01-080-4479>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**First Flat Length:**

0.250 inches

**Flat Height:**

Between 0.092 inches and 0.096 inches

**Body Diameter:**

0.625 inches

**Shaft Diameter:**

Between 0.124 inches and 0.126 inches

**Shaft Length:**

Between 0.984 inches and 1.016 inches

**Body Length:**

1.000 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

4.50 inch-ounces

**Maximum Running Torque:**

4.50 inch-ounces

**Maximum Stop Torque:**

32.00 inch-ounces

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Mounting Method:**

Standard bushing w/shaft seal

**Electrical Resistance Per Section:**

25.000 kilohms all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 all sections

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Standard Taper Curve Per Section:**

K all sections

**Terminal Type And Quantity:**

4 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0