Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-080-9790

# Section Quantity:

2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.094 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.266 inches Shaft Style: Round, slotted

Actuator Type:

Single shaft

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

0.531 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:** 

250.000 kilohms all sections

#### **Rotary Actuator Travel In Angular Deg:**

Between 309.0 and 320.0

### **Resistance Tempurature Characteristic Range Per Section In Percent:**

-3.0/+0.0 -55 degrees celsius all sections and -5.0/+10.0 -25 degrees celsius all sections and -5.0/+10.0 25 degrees celsius all sections and

+0.0/+3.0 120 degrees celsius all sections

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

# NSN 5905-01-080-9790

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

# Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

## Standard Taper Curve Per Section:

A all sections

## Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

6 tab, solder lug

#### **Specification Data:**

81349-mil-r-94/6 government specification

Shelf Life:

N/a

Unit Of Measure:

# --

Demilitarization:

No

# Fiig:

A002a0