

View Online at <https://aerobasegroup.com/nsn/5905-01-081-3478>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

1.000

Overall Length:

1.308 inches

Terminal Length:

0.500 inches

Overall Height:

0.815 inches

Overall Width:

0.190 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.058 inches

Body Length:

1.250 inches

Body Width:

0.190 inches

Body Height:

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9720.0

Center To Center Distance Between Terminals:

0.700 inches

Fragility Factor:

Moderately delicate

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal and unthreaded hole

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Humidity proof

Electrical Resistance Per Section:

2.000 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

9720.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-39035/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0