Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-081-3643

Section (	zuanny:
1	
Body Sty	'le:
Rectangu	lar
Reliabilit	y Indicator:
Not estab	lished
Terminal	Length:
0.187 inc	nes
Shaft Dia	meter:
0.062 inc	nes
Shaft Lei	ngth:
Between	0.040 inches and 0.060 inches
Body Lei	ngth:
0.250 inc	nes
Body Wi	dth:
0.188 inc	nes
Body He	ight:
0.250 inc	hes
Shaft Sty	'le:
Round, s	lotted
Actuator	Туре:
Single sh	aft
Effective	Electrical Rotation In Deg Angular Rotation:
7920.0	
Maximun	n Starting Torque:
5.00 inch	ounces
Maximun	n Running Torque:
5.00 inch	ounces
Center T	o Center Distance Between Terminals:
0.200 inc	hes
Terminal	Location:
Right adja	acent side two rows
Mounting	g Method:
Terminal	
Center T	o Center Distance Between Terminal Rows:
0.100 inc	hes
Electrica	I Resistance Per Section:
25.0 kiloh	ms single section
Rotary A	ctuator Travel In Angular Deg:
7920.0	
Center T	o Center Distance Between Center Terminal And Outside Termin
0.400 :===	

0.100 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0