

View Online at <https://aerobasegroup.com/nsn/5905-01-081-3665>

**Section Quantity:**

2

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**Shaft Diameter:**

Between 0.124 inches and 0.126 inches

**Shaft Length:**

Between 0.994 inches and 1.056 inches

**Mounting Bushing Length:**

Between 0.234 inches and 0.266 inches

**Body Length:**

Between 1.903 inches and 1.997 inches

**Body Width:**

0.625 inches

**Body Height:**

0.625 inches

**Undercut Diameter:**

Between 0.077 inches and 0.079 inches

**Shaft Style:**

Round, stepped

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

Any acceptable

**Actuator Type:**

Dual concentric

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.305 inches

**Switch Operating Position:**

End of rotation

**Switch Contact Arrangement:**

Double pole, single throw, one open, one closed

**Undercut Length:**

0.525 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Top and bottom

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

5.000 kilohms all sections

**Power Dissipation Rating Per Section In Watts:**

0.5 free air all sections

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Switch Current Type And Rating In Amps:**

Any acceptable

**Standard Taper Curve Per Section:**

A all sections

**Special Features:**

4pst push-pull switch 2no-2nc

**Terminal Type And Quantity:**

18 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0