

View Online at <https://aerobasegroup.com/nsn/5905-01-081-5037>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

liilength:

0.300 inches

Terminal Length:

0.188 inches

liiheight:

0.543 inches

liiwidth:

0.312 inches

Body Length:

0.300 inches

Body Width:

0.312 inches

Body Height:

0.355 inches

Shaft Bearing Type:

Bearing

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

285.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

0.10 inch-ounces

Maximum Stop Torque:

15.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

285.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0 to 150.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0