Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-081-6083

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Terminal Length:** Between 0.470 inches and 0.530 inches Mounting Hole Diameter: 0.093 inches Shaft Diameter: 0.100 inches Shaft Length: Between 0.036 inches and 0.080 inches **Body Length:** 1.250 inches **Body Width:** 0.190 inches **Body Height:** Between 0.300 inches and 0.330 inches Shaft Style: Round, slotted Shaft Bearing Type: Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.700 inches

Fragility Factor:

Moderately rugged

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side two rows

NSN 5905-01-081-6083 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



lounting Method:	
erminal and unthreaded hole	
enter To Center Distance Between Terminal Rows:	
100 inches	
eatures Provided:	
umidity proof	
ubic Measure:	
074 cubic inches	
lectrical Resistance Per Section:	
5.0 percent, rated amperes c and better flooring	
otary Actuator Travel In Angular Deg:	
920.0	
enter To Center Distance Between Center Terminal And Outside Terminal:	1
300 inches	
mbient Tempurature In Deg Celsius Per Section At Zero Percent Rated Po	wer:
50.0 single section	
empurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius	:
00.0/+100.0 single section	
ower Dissipation Rating Per Section In Watts:	
0 7th secondary quality	
esistance Tolerance Per Section In Percent:	
0.0/+10.0 single section	
ctuator Travel Control Feature:	
lutch	
mbient Tempurature In Deg Celsius Per Section At Full Rated Power:	
0.0 single section	
tandard Taper Curve Per Section:	
single section	
erminal Type And Quantity:	
pin	
helf Life:	
/a	
nit Of Measure:	
emilitarization:	
0	
iig:	
002a0	