

View Online at <https://aerobasegroup.com/nsn/5905-01-082-0866>

Section Quantity:

2

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

Between 0.889 inches and 0.951 inches

Mounting Bushing Length:

Between 0.234 inches and 0.266 inches

Body Length:

Between 1.000 inches and 1.094 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Undercut Diameter:

Between 0.077 inches and 0.079 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Maximum Starting Torque:

4.00 inch-ounces

Maximum Running Torque:

0.10 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.305 inches

Undercut Length:

0.295 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.000 kilohms all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

F 2nd section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0