NSN 5905-01-082-5270

Single inline

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-082-5270

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|
| -250.0/+250.0 |
| Electrical Resistance: |
| 2.200 kilohms |
| Resistance Tolerance In Percent: |
| -2.000/+2.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 8 |
| Terminal Type: |
| Pin |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.125 inches |
| Body Length: |
| 0.778 inches |
| Body Width: |
| 0.090 inches |
| Body Height: |
| 0.250 inches |
| Schematic Diagram Designator: |
| Ladder network |
| Power Dissipation Rating In Watts: |
| 0.125 total network |
| End Application: |
| Ticonderoga class cg (47), sturgeon class ssn (637), nimitz class cvn, virginia class sgn (41), forrestal class cv, spruance class dd (963). |
| los angeles class ssn (688), austin ship class lpd-4 amphibious transport docks. Landing craft air cushion (lcac). |
| Identical Value Resistor Quantity: |
| 7 each resistor |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Weapon system essential |
| Style Designator: |

NSN 5905-01-082-5270

Film Fixed Resistor Network - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| CI | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0