## NSN 5905-01-082-7317

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-082-7317 **Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Mounting Bushing Length:** 0.750 inches **Body Length:** 8.875 inches **Body Width:** Between 3.469 inches and 3.531 inches **Body Height:** Between 5.219 inches and 5.281 inches **Shaft Bearing Type:** Sleeve **Actuator Type:** Integral knob **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 1.250 inches **Fragility Factor:** Rugged **End Application:** Test set power supply model da675-msm **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Cubic Measure:** 166.072 cubic inches **Electrical Resistance Per Section:** 4.0 ohms all sections **Actuator Travel Control Feature:** Stops **Standard Taper Curve Per Section:** A all sections

**Terminal Type And Quantity:** 3 threaded stud

## NSN 5905-01-082-7317

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Shelf Life:       |
|-------------------|
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |

A002a0