Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-082-7317

# Section Quantity:

2

Body Style:

Rectangular bushing mounted

# Reliability Indicator:

Not established

# Mounting Bushing Length:

0.750 inches

### Body Length:

8.875 inches

### Body Width:

Between 3.469 inches and 3.531 inches

### **Body Height:**

Between 5.219 inches and 5.281 inches

# Shaft Bearing Type:

Sleeve

# Actuator Type:

Integral knob

### Nonturn Device Location:

At 3 oclock and at 9 oclock

# Nonturn Device Radius:

1.250 inches

### Fragility Factor:

Rugged

# End Application:

Test set power supply model da675-msm

### **Terminal Location:**

Rear end

# Mounting Method:

Standard bushing

### **Features Provided:**

Humidity proof

### **Cubic Measure:**

166.072 cubic inches

### **Electrical Resistance Per Section:**

4.0 ohms all sections

# **Actuator Travel Control Feature:**

Stops

### **Standard Taper Curve Per Section:**

A all sections

# Terminal Type And Quantity:

3 threaded stud

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0