NSN 5905-01-083-2144

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-083-2144

Section Overtity:
Section Quantity:
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.380 inches
Flat Height:
0.216 inches
Body Diameter:
Between 1.079 inches and 1.109 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
0.505 inches
Mounting Bushing Length:
Between 0.344 inches and 0.390 inches
Body Length:
0.588 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.0 ohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:

3 eyelet

-10.0/+10.0 single section

Terminal Type And Quantity:

NSN 5905-01-083-2144

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0