Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-083-2144

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### First Flat Length:

0.380 inches

#### Flat Height:

0.216 inches

Body Diameter:

Between 1.079 inches and 1.109 inches

#### Shaft Diameter:

Between 0.248 inches and 0.251 inches

### Shaft Length:

0.505 inches

#### Mounting Bushing Length:

Between 0.344 inches and 0.390 inches

#### Body Length:

0.588 inches

#### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

25.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

# Terminal Type And Quantity:

3 eyelet

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0