NSN 5905-01-083-3746

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-083-3746

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -25.0/+25.0 Electrical Resistance: 21.740 kilohms Resistance Tolerance In Percent: -0.050/+0.050 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length:
Electrical Resistance: 21.740 kilohms Resistance Tolerance In Percent: -0.050/+0.050 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
21.740 kilohms Resistance Tolerance In Percent: -0.050/+0.050 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Resistance Tolerance In Percent: -0.050/+0.050 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches
Body Diameter: Between 0.078 inches and 0.140 inches
Between 0.078 inches and 0.140 inches
Body Length:
Between 0.204 inches and 0.281 inches
Power Dissipation Rating In Watts:
0.100 free air
Style Designator:
Axial terminal each end
Axial terminal each end Shelf Life:
Shelf Life:
Shelf Life: N/a
Shelf Life: N/a
Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure: Demilitarization:
Shelf Life: N/a Unit Of Measure: Demilitarization: No