## NSN 5905-01-084-2924

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-084-2924 **Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.094 inches **Overall Height:** 0.875 inches **Overall Width:** 0.625 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.063 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.031 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 

0.50 inch-ouncesMaximum Stop Torque:64.00 inch-ounces

Nonturn Device Location:

At 9 oclock

## NSN 5905-01-084-2924

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Nonturn Device Radius:
0.305 inches
Fragility Factor:
Rugged
Jndercut Length:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Cubic Measure:
0.403 cubic inches
Electrical Resistance Per Section:
10.000 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
5.5/+5.5 -55 degrees celsius 2nd section and -3.0/+3.0 -25 degrees celsius 2nd section and -1.5/+1.5 0 degrees celsius 2nd section and
3.0/+3.0 85 degrees celsius 2nd section and -5.0/+5.0 120 degrees celsius 2nd section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Resistance Tolerance Per Section In Percent:
10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Ferminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
_

No

Demilitarization:

## NSN 5905-01-084-2924

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0