NSN 5905-01-084-7045

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-084-7045

Section Quantity:
1
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Shaft Diameter:
0.125 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.469 inches
Body Width:
0.469 inches
Body Height:
0.735 inches
Shaft Style:
Round
Switch Type:
Rotary
Switch Voltage Rating In Volts:
120.0 and 28.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
275.0
Maximum Starting Torque:
13.00 inch-ounces
Maximum Running Torque:
13.00 inch-ounces
Nonturn Device Location:
At 1 0clock
Nonturn Device Radius:
0.245 inches
Mechanical Backlash In Deg Angular Rotation:
3.0
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single note single throw normally open, both positions mainta

NSN 5905-01-084-7045

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+4.5 -55 degrees celsius single section and +0.0/+2.5 -25 degrees celsius single section and +0.0/+1.5 0 degrees celsius single section
and -1.5/+1.5 85 degrees celsius single section and +0.0/+3.5 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
0.500 ac and 1.500 dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fila·