NSN 5905-01-084-9937

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-084-9937 **Section Quantity:** 1 **Body Style:** 42b rectangular w/bushing/hole mounting **Reliability Indicator:** Not established **Shaft Diameter:** 0.093 inches **Shaft Length:** 0.344 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 0.562 inches **Body Width:** 0.420 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces

| 5.00 Inter-ourides |
|------------------------------------|
| Maximum Running Torque: |
| 5.00 inch-ounces |
| Screw Thread Diameter: |
| 0.190 inches |
| Screw Thread Series Designator: |
| Jnf |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 100.0 kilohms single section |
| |
| |
| |

NSN 5905-01-084-9937

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Rotary Actuator Travel In Angular Deg: |
|---|
| 9000.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -70.0/+70.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |