NSN 5905-01-084-9939

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-084-9939 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.906 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 1.375 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.750 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 0.30 inch-ounces **Maximum Running Torque:** 0.25 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.312 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:**

Shaft Radial Play: 0.002 inches Mechanical Backlash In Deg Angular Rotation:

0.001 inches

NSN 5905-01-084-9939

Demilitarization:

Precision Wire Wound Variable Resistor - Page 2 of 3



Screw Thread Diameter:	
0.250 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0 	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Standard bushing	
Electrical Resistance Per Section:	
1.5 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
-1.00/+1.00 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-1000.0/+1000.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.25 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Test Data Document:	
81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
3 turret	
Specification Data:	
81349-mil-r-12934/10 government specification	
Shelf Life:	
N/a	
Unit Of Meacure:	

NSN 5905-01-084-9939

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0