NSN 5905-01-085-2021

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-085-2021

Electrical Resistance: 390.090 ohms Resistance Tolerance In Percent: 2,000/4-2,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 nciosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Rody Diameter: 1,190 inches Rody Length: 1,562 inches Power Dissipation Rating In Watts: 1,000 rea air Style Designator: Axial terminal each end Test Data Document: 131349-mill-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain invincemental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Demilitarization: No	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 2.0004-2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Temp	-200.0/+200.0
Resistance Tolerance in Percent: 2.000/+2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+150.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 1.000 Boddy Diameter: 2.190 inches Boddy Diameter: 2.190 inches Boddy Length: 2.562 inches Power Dissipation Rating in Watts: 1.000 free air Style Dasignator: Avial terminal each end Test Data Document: 131349-milt-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ermat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheft Life: Via Duint Of Measure:	Electrical Resistance:
2.000/42.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Incapsulated Impurature Rate Level In Percent: Incapsulated Impurature Rate Level In Percent: Incoo Body Diameter: Incoo Body Diam	390.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.00 Tempurature Range Of Tempurature Release States Stat	-2.000/+2.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 380dy Diameter: 1.190 inches 380dy Length: 1.052 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Aktal terminal each end Test Data Document: 31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain service ments and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: We Unit Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.04-150.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Reliability Failure Rate Level In Percent: 1.000 Saddy Dameter: 1.190 inches Body Dameter: 1.190 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wie Unit Of Measure:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 131349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 21349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure:	150.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Body Diameter: 0,190 inches Body Length: 0,562 inches Power Dissipation Rating In Watts: 1,000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mill-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formati; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 1.190 inches Body Length: 1.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 131349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure:	-55.0/+150.0
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 1.190 inches Body Length: 1.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Body Diameter: 0,190 inches Body Length: 0,562 inches Power Dissipation Rating In Watts: 1,000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Encapsulated
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: Demilitarization: No	Terminal Type:
Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization:	Wire lead
Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization:	Reliability Indicator:
Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Established
Body Length: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Reliability Failure Rate Level In Percent:
20.190 inches Body Length: 20.562 inches Power Dissipation Rating In Watts: 20.1000 free air Style Designator: Avial terminal each end Fest Data Document: 20.1349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization:	1.000
Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.190 inches
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure:	Body Length:
Style Designator: Axial terminal each end Test Data Document: B1349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.562 inches
Axial terminal each end Test Data Document: 31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: B1349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	1.000 free air
Test Data Document: 81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Style Designator:
B1349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A001a0	A001a0