## NSN 5905-01-085-3197

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-085-3197

-25.0/+25.0  Electrical Resistance: 4.497 kilohms  Resistance Tolerance In Percent: -0.050/+0.050  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010  Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 4.497 kilohms Resistance Tolerance In Percent: -0.050/+0.050 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	•
4.497 kilohms  Resistance Tolerance In Percent: -0.050/+0.050  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.010  Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end Shelf Life: N/a	
Resistance Tolerance In Percent: -0.050/+0.050 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010  Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.010  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.078 inches and 0.140 inches  Body Length: Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Shelf Life: N/a	-
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
-55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.010  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.078 inches and 0.140 inches  Body Length: Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Shelf Life: N/a	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	
Established  Reliability Failure Rate Level In Percent:  0.010  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.078 inches and 0.140 inches  Body Length: Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Wire lead
Reliability Failure Rate Level In Percent:  0.010  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.078 inches and 0.140 inches  Body Length: Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Reliability Indicator:
O.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.078 inches and 0.140 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: O.100 free air Style Designator: Axial terminal each end Shelf Life: N/a	Established
Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.078 inches and 0.140 inches  Body Length: Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Shelf Life: N/a	Reliability Failure Rate Level In Percent:
Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.078 inches and 0.140 inches  Body Length:  Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	0.010
Body Diameter:  Between 0.078 inches and 0.140 inches  Body Length:  Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Terminal Length:
Between 0.078 inches and 0.140 inches  Body Length:  Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Between 1.375 inches and 1.625 inches
Body Length:  Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Body Diameter:
Between 0.204 inches and 0.281 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Between 0.078 inches and 0.140 inches
Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Body Length:
0.100 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Between 0.204 inches and 0.281 inches
Style Designator:  Axial terminal each end  Shelf Life:  N/a	Power Dissipation Rating In Watts:
Axial terminal each end  Shelf Life: N/a	0.100 free air
Shelf Life: N/a	Style Designator:
N/a	Axial terminal each end
	Shelf Life:
	N/a
Unit Of Measure:	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0