Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-085-6182

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

2.000 inches

### Shaft Diameter:

0.2497 inches

## Shaft Length:

0.875 inches

### Mounting Bushing Length:

0.375 inches

### Body Length:

0.905 inches

#### Shaft Style:

Round

## Shaft Bearing Type:

Ball

### Actuator Type:

Double ended shaft

## Effective Electrical Rotation In Deg Angular Rotation:

350.0

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

1.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

360.0

# Function Conformity Tolerance Per Section:

-0.10/+0.10 single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section



**Power Dissipation Rating Per Section In Watts:** 8.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 turret Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0