

View Online at <https://aerobasegroup.com/nsn/5905-01-085-6397>

Section Quantity:

1

Body Style:

Rectangular w/mounting hole/slot

Reliability Indicator:

Not established

Overall Length:

0.741 inches

Terminal Length:

0.290 inches

Overall Height:

0.391 inches

Overall Width:

0.219 inches

Mounting Hole Diameter:

0.074 mils

Shaft Diameter:

0.090 inches

Shaft Length:

0.040 inches

Body Length:

0.391 inches

Body Width:

0.219 inches

Body Height:

0.391 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately rugged

Mounting Facility Quantity:

1

Terminal Location:

Rear end

Mounting Method:

Terminal and unthreaded hole

Features Provided:

Humidity proof

Cubic Measure:

0.033 cubic inches

Electrical Resistance Per Section:

10.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 7th secondary quality

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0