## NSN 5905-01-085-8054

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-085-8054 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.625 inches **Shaft Diameter:** 0.124 inches **Shaft Length:** 0.593 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.065 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.000 ohms all sections **Rotary Actuator Travel In Angular Deg:** 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections

120.0 an 000.01.0

Power Dissipation Rating Per Section In Watts:

1.0 free air all sections

## NSN 5905-01-085-8054

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No