

View Online at <https://aerobasegroup.com/nsn/5905-01-085-8334>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7500 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

0.984 inches

**Undercut Diameter:**

0.760 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

0.875 inches

**Shaft Diameter:**

0.1248 inches

**Shaft Length:**

0.500 inches

**Body Length:**

0.484 inches

**Overall Diameter:**

0.875 inches

**Mounting Lip Diameter:**

0.8750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

340.0

**Maximum Starting Torque:**

0.50 inch-ounces

**Maximum Running Torque:**

0.50 inch-ounces

**Shaft End Play:**

0.00500 inches

**Shaft Runout:**

0.001 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.00100 inches

**Shaft Radial Play:**

0.005 inches

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.338 cubic inches

**Electrical Resistance Per Section:**

5.000 percent, rated amperes c and better flooring

**Tap Location From Cw Terminal Per Section In Deg Of Effective Electrical Rotation:**

170.0 single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Resistance Temperature Characteristic Range Per Section In Percent:**

-5.0/+5.0 -65 degrees celsius single section and -2.5/+2.5 0 degrees celsius single section and -5.0/+5.0 75 degrees celsius single section  
and -5.0/+5.0 125 degrees celsius single section

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 7th secondary quality

**Function Conformity Per Section:**

Single section independent linearity

**Fixed Tap Quantity Per Section:**

1 single section

**Tap Location Tolerance Per Section:**

-0.5/+0.5 degrees angular rotation single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

7 oclock all primaries

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Terminal Type And Quantity:**

4 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0