Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-086-8354

Section	Quantity:	

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.187 inches

**Body Length:** 

0.315 inches

**Body Width:** 

0.312 inches

**Body Height:** 

0.375 inches

Actuator Type:

Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

1440.0

**Center To Center Distance Between Terminals:** 

0.100 inches

**Terminal Location:** 

Lower adjacent side single row

Mounting Method:

Terminal

**Electrical Resistance Per Section:** 

1.000 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

## Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 pin

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0