## NSN 5905-01-086-8496

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-086-8496 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.640 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.375 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.656 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:
--

## NSN 5905-01-086-8496

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A002a0