Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-086-9107

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

0.500 inches

#### Shaft Diameter:

0.250 inches

### Shaft Length:

1.000 inches

### Body Length:

1.500 inches

### Shaft Style:

Round

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

4320.0

## Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.125 inches

### Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

## **Mounting Method:**

Standard bushing

# **Features Provided:**

Hermetically sealed

# **Electrical Resistance Per Section:**

50.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

4320.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section



#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-25.0/+25.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

# **Actuator Travel Control Feature:**

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

### Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

2 tab, solder lug

#### Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

# Fiig:

A002a0