

View Online at https://aerobasegroup.com/nsn/5905-01-086-9271

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

1.556 inches

#### **Body Diameter:**

0.875 inches

### Shaft Diameter:

0.125 inches

### Shaft Length:

0.875 inches

### Mounting Bushing Length:

# 0.188 inches

**Body Length:** 

0.681 inches

Shaft Style:

Round, slotted

### Shaft Bearing Type:

Bearing

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

340.0

### Maximum Starting Torque:

8.00 inch-ounces

### Maximum Running Torque:

8.00 inch-ounces

### Shaft End Play:

0.003 inches

#### Shaft Runout:

0.001 inches

### Shaft Radial Play:

0.003 inches

### Screw Thread Diameter:

0.375 inches

# Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0



<b>-</b>
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
340.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Precious Material And Location:
Terminal surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0