NSN 5905-01-087-0734

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-087-0734 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6250 inches Pilot Length: 0.0620 inches **Overall Length:** 1.945 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.375 inches **Body Length:** 1.570 inches **Overall Diameter:** 1.000 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Effective Electrical Rotation In Deg Angular Rotation:**

Shaft Bearing Type: Ball **Actuator Type:** Single shaft 3600.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces

NSN 5905-01-087-0734

Maximum Stop Torque:

Precision Wire Wound Variable Resistor - Page 2 of 3



128.00 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Rugged
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Cubic Measure:
0.944 cubic inches
Electrical Resistance Per Section:
2.0 percent, rated amperes c and better flooring
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
1800.0 single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.5 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Clutch

7 oclock all primaries

NSN 5905-01-087-0734

No Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 3 of 3



Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
60.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: