NSN 5905-01-087-0735

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-087-0735 **Section Quantity: Body Style:** Rectangular w/bushing/slot mounted **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.312 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.468 inches **Body Width:** 0.282 inches **Body Height:** 0.453 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 0.10 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 0.375 inches **Screw Thread Diameter:** 0.190 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:**

Terminal Location:

Rear end

NSN 5905-01-087-0735

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing and unthreaded hole
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0