## NSN 5905-01-087-1910

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-087-1910 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.522 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 0.720 inches **Overall Diameter:** 1.070 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces

**Shaft End Play:** 0.010 inches **Shaft Runout:** 0.003 inches **Lateral Runout:** 0.005 inches **Pilot Diameter Runout:** 0.003 inches **Shaft Radial Play:** 0.003 inches

## NSN 5905-01-087-1910

Precision Wire Wound Variable Resistor - Page 2 of 3



Fragility Factor:
Rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Precious Material And Location:
Plated terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5905-01-087-1910

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0