Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-087-3674

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# Reliability Indicator:

Not established

### **Body Diameter:**

0.500 inches

#### Shaft Diameter:

0.125 inches

### Mounting Bushing Length:

0.250 inches

### **Body Length:**

0.500 inches

### Shaft Style:

Round

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

295.0

## Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

#### Terminal Location:

Rear end

#### **Mounting Method:**

Standard bushing

#### **Rotary Actuator Travel In Angular Deg:**

295.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Power Dissipation Rating Per Section In Watts:

0.750 free air single section

# Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

#### Standard Taper Curve Per Section:

A single section



## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0