

View Online at https://aerobasegroup.com/nsn/5905-01-087-5720

# Section Quantity:

1

Body Style:

Rectangular

# **Reliability Indicator:**

Not established

#### **Overall Length:**

0.400 inches

#### Terminal Length:

0.150 inches

#### **Overall Height:**

0.400 inches

#### **Overall Width:**

0.400 inches

#### Body Length:

#### 0.250 inches

#### **Body Width:**

0.400 inches

# Body Height:

0.400 inches

#### Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

290.0

#### Maximum Starting Torque:

5.00 inch-ounces

#### Maximum Running Torque:

5.00 inch-ounces

#### Center To Center Distance Between Terminals:

0.200 inches

#### **Fragility Factor:**

Moderately delicate

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Terminal

#### **Features Provided:**

Humidity proof

#### **Cubic Measure:**

0.040 cubic inches

## **Electrical Resistance Per Section:**

50.000 ohms c and better flooring

# NSN 5905-01-087-5720

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

360.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0