NSN 5905-01-087-8368

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-087-8368 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.062 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.562 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.500 inches **Body Width:** 0.516 inches **Body Height:** 0.516 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 265.0 **Maximum Starting Torque:** 4.50 inch-ounces **Maximum Running Torque:** 4.50 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Screw Thread Diameter:** 0.250 inches

Screw Thread Series Designator: Screw Thready Qty Per Inch (tpi):

Terminal Location:

32.0

Lower adjacent side single row

Mounting Method: Standard bushing

NSN 5905-01-087-8368

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0