

View Online at <https://aerobasegroup.com/nsn/5905-01-088-1485>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.234 inches

Body Diameter:

1.094 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.500 inches

Body Length:

0.609 inches

Overall Diameter:

1.484 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 309.0 and 320.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing w/panel seal and locking bushing w/shaft seal

Features Provided:

Humidity proof

Cubic Measure:

0.572 cubic inches

Electrical Resistance Per Section:

1.500 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Resistance Temperature Characteristic Range Per Section In Percent:

-3.0/+0.0 -55 degrees celsius single section and -5.0/+10.0 -25 degrees celsius single section and -5.0/+10.0 25 degrees celsius single section and +0.0/+3.0 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Unpackaged Unit Weight:

0.80 ounces

Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-94/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Fig:

A002a0