NSN 5905-01-089-5975

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-089-5975

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 50.0/+50.0 Electrical Resistance: 221.000 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Body Diameter: .109 inches
Electrical Resistance: 121.000 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Telescore Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:000 Body Diameter:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Body Diameter:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Vire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Body Diameter: 0.109 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Body Diameter:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Body Diameter: .109 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Rody Diameter: 2.109 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Body Diameter:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Body Diameter: .109 inches
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:000 Body Diameter: 0.109 inches
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:000 Body Diameter: 0.109 inches
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:000 Body Diameter: 0.109 inches
Encapsulated Ferminal Type: Vire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Body Diameter: 0.109 inches
Ferminal Type: Vire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Rody Diameter: 0.109 inches
Vire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: .000 Body Diameter: 0.109 inches
Established Reliability Failure Rate Level In Percent: .000 Body Diameter: 0.109 inches
Established Reliability Failure Rate Level In Percent: .000 Body Diameter: 0.109 inches
.000 Body Diameter: 0.109 inches
.000 Body Diameter: 0.109 inches
0.109 inches
Pady Langth
Body Length:
0.250 inches
Power Dissipation Rating In Watts:
0.100 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
_
Demilitarization:
No
Fiig:
A001a0