## NSN 5905-01-089-7897

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-089-7897 **Section Quantity: Body Style:** Rectangular w/mounting holes **Terminal Length:** 0.500 inches **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.035 inches **Body Length:** 0.500 inches **Body Width:** 0.220 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Center To Center Distance Between Terminals:** 0.200 inches **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 2.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.100 inches

## NSN 5905-01-089-7897

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No