

View Online at https://aerobasegroup.com/nsn/5905-01-089-8722

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

2.8750 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

2.850 inches

Undercut Width:

0.0730 inches

Body Diameter:

3.000 inches

Shaft Diameter:

Between 0.1869 inches and 0.1872 inches

Shaft Length:

0.630 inches

Body Length:

0.970 inches

Mounting Lip Diameter:

3.0000 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

351.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft End Play:

0.002 inches

Shaft Runout:

0.001 inches



Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
0.1
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
175.5 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
7.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-0.5/+0.5 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
60.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:

N/a



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0