NSN 5905-01-090-3004

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-090-3004

1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.300 inches
Shaft Diameter:
0.065 inches
Shaft Length:
0.040 inches
Body Length:
0.250 inches
Body Width:
0.165 inches
Body Height:
0.250 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
4320.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
50.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
4320.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section

NSN 5905-01-090-3004

Demilitarization:

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
35.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
30003-247as-c2607 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-